

Goodflex are experts in the design, manufacture and supply of rubber hoses, assemblies and mouldings with the widest range of rubbers available in the UK.

Our customers choose us because we can quickly understand their exact requirements for dimensions, temperature range, operating temperatures and resistance to various mediums, and as we have the fastest product turnaround in the industry.

Vital to our customers' success is our wealth of experience, expertise and our modern manufacturing facility which enables us to control every aspect of the design, prototyping and production process.

Goodflex offers the complete solution.

## Superflex Hose

Superflex Hoses can be easily fitted onto applications which may otherwise have required a shaped hose, therefore avoiding the cost for tooling.

The highly flexible wire reinforced hose is designed to withstand pressure and also prevent collapsing under vacuum.

A quick fit solution with all the quality and performance of a silicone hose.

Choosing silicone for the integral liner gives the option to make the hose oil/fuel resistant, FDA approved or fire retardant.

Available in a range of bore sizes and lengths, with 1 metre being the most cost effective option.

Temperature Range: -70°C - +170°C

Bore Size Range: 13mm - 60mm

(larger sizes are available however the unique flexibility properties begin to dissipate as the bore size increases)

Colour: Various

ID Internal Diameter (mm)	Typical Weight (kg/m)	Typical Bending Radius	Burst Pressure (Bar)
12.7	0.4	70	20
16	0.478	75	20
19	0.5	80	20
22	0.6	90	20
25.4	0.7	95	20
28	0.75	100	15
30	0.79	105	15
32	0.85	115	15
35	0.92	125	15
38	0.97	175	15
41	1.1	250	15
45	1.15	375	15
48	1.2	525	15
51	1.4	1100	10
55	1.5	1200	10
57	1.6	1300	10
60	1.7	1700	10

